

## Declaration of Performance (DoP)

oduct Type:	Insert appliance (with surround made of soapstone)	
ype, batch or serial number:	Jøtul FS 173	
ntended use of the product:	Insert burning solid fuel without water supply	
lame and Address of the manufacturer:	Jøtul AS	
	Postboks 1411, 1602 Fredrikstad, Norway	
	Tel.: +47 69 35 90 00	
	E-mail: post@jotul.no	
NVCP:	System 3	
ystem(s) of assessment and verification of constancy op performance (AVCP) of the construction product as set out in		
CPR, Annex V		
lotified body:	Danish Technological Institute	
NB-No:	1235	
Test report no:	300-ELAB-1835-EN ENG rev 1, ELAB 1835-MUR	
Declared performance:		
Harmonized technical specification	EN 13229:2001/A2:2004/AC:2007	
Essential characteristics	Performance	
Fire safety		
Reaction to fire	A1	
Distance to combustible materials	Minimum distances, in mm	
	Side =	700
	Rear =	70
	Ceiling =	650
	0	
	Front =	1000
Risk of burning fuel falling out	No	
Emission of combustion products	CO	[0,07 %]
	NOx	[54 mg/m3]
	OGC	[60 mgC/m3]
Conference and the	PM	[14 mg/m3]
Surface temperature Electrical safety	Pass	
Cleanability	- Pass	
	-	
Maximum water operating pressure		
Flue gas temperature at nominal heat output Mechanical resistance (to carry a chimney/flue)	T [305°C] NPD	
Thermal output	7 1.34/	
Normal heat output	7 kW	
Room boating output	- kW	
Room heating output Water heating output	-*kW	

## Declaration:

The performance of the product in conformity with the declared performance. This declaration of performance is issued under the sole responsibility of the manufacturer.

Signed on behalf of the manufacturer:

Tom J. Berglind

R&D Manager

(Name and function)

Fredrikstad, September 25th 2013

(Place and date of issue)

Jon J. Berghind (signature)